

Full Size Trucks Demo Derby Rules

If it isn't in the rules, you cannot do it. Ask First!

All Truck/Van/SUV's must be 2WD only. No Super Duty/HD/Excursions allowed. Front Drive shaft must be removed.

1. Battery must be relocated to front passenger floorboard. 1 or 2 batteries allowed.
2. A 4-point cage is highly recommended. Cages must not exceed 6" in front of the door and may not exceed past the cab 6"
3. Truck beds may have a total of 10 body bolts with plates not exceeding 6". Bolts or rods can be welded alongside of the frame. NO WEDGE BEDS
4. Cab can be bolted to box in 2 places with 6" plates.
5. Tailgates must be in upright stock location and can be dropped to be used as a bumper – 8" MAX
6. Stock gas tanks should be removed, and boat tank or fuel cell mounted in back seat or front of box – securely fastened. All fittings should be leak proof.
7. All OEM Bumpers allowed. No Chrysler pointy bumpers. A 2"x 6" square tube ¼" thick can be used in place of bumper. When welding on bumper bracket – no more than 6" into frame. No stuffed bumpers. Bumper height – 26" high and 19" low.
8. Clamping of leave springs is allowed. 4 per side – no converting a coil front to a leaf.
9. After market steering/pedals/slider driver shafts/shifters are allowed.
10. 4 bolts or ready rods to hold hood down. 2 through radiator support and 2 sheet metal to sheet metal.
11. Motor may interchange, no distributor protectors or transmission braces. Basic lower engine cradle is allowed.
12. Radiators in stock locations. Stock or aftermarket – no radi barrels. Wire mesh is allowed for a radiator protector 1/8" thick
13. Doors must be welded or chained. 2 straps – 6" per seam
14. Any rear end. No Bracing. Can run 1 – 3/8" chain per side to hold rear end in.
15. 2 straps or chains in front window
16. No plated frames on fresh trucks. Fix-it plates 4"x 12" per side and must be clearly visible that it was bent. No stacking plates over the top of each other.